

In re Patent Application of:
MARTAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

In the Claims:

Claims 1-4 (Cancelled).

5. (Currently amended) A computer system comprising:
a master apparatus; and
a slave apparatus for communicating with said master
apparatus and communicating via a universal serial bus (USB)
protocol, said slave apparatus comprising

a sending/receiving circuit for sending and
receiving binary information to and from said master
apparatus and supplying status signals based thereon,
~~and for acknowledging and recording a new message only
when a transfer interruption signal is not supplied,~~

a plurality of state latches and control circuitry
cooperating therewith for receiving the status signals
from said sending/receiving circuit and supplying state
signals of said sending/receiving circuit based
thereon,

a microprocessor for processing applications of
said slave apparatus and also for processing the binary
information received by said sending/receiving circuit
when an interruption signal is supplied, and

an interruption state latch and a control circuit
cooperating therewith for supplying an interruption
signal to said microprocessor once the ~~end of a message
has been acknowledged and for supplying the transfer~~

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

~~interruption signal to said microprocessor once the~~
~~start of a new message has been acknowledged and~~
~~recorded by said sending/receiving circuit when the~~
~~microprocessor interruption signal is supplied.~~
said sending/receiving circuit also acknowledging
the start of a following message while the interruption
signal is supplied.

6. (Previously presented) The computer system of Claim 5 wherein said control circuit for controlling said interruption state latch comprises at least one logic circuit for receiving the status signals from said sending/receiving circuit and setting said interruption state latch to a predetermined logic level to indicate a microprocessor interruption request.

7. (Previously presented) The computer system of Claim 5 wherein said control circuitry for controlling said state latches prevents the binary information from said sending/receiving circuit from being written into said plurality of state latches during receipt of the start of the new message and during the presence of the interruption signal.

8. (Previously presented) The computer system of Claim 5 wherein said master apparatus comprises a central processing unit.

9. (Previously presented) The computer system of Claim 5 wherein said slave apparatus comprises a computer peripheral

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

device.

10. (Previously presented) The computer system of Claim 5 further comprising a cable connecting said master apparatus and said slave apparatus.

11. (Currently amended) A computer system comprising:
a master apparatus; and
a slave apparatus for communicating with said master apparatus and comprising

a sending/receiving circuit for sending and receiving binary information to and from said master apparatus and supplying status signals based thereon, ~~and for acknowledging and recording a new message only when a transfer interruption signal is not supplied,~~

a plurality of state latches and control circuitry cooperating therewith for receiving the status signals from said sending/receiving circuit and supplying state signals of said sending/receiving circuit based thereon,

a microprocessor for processing applications of said slave apparatus and also for processing the binary information received by said sending/receiving circuit when an interruption signal is supplied, and

an interruption state latch for supplying an interruption signal to said microprocessor once the end ~~of a message has been acknowledged and for supplying the transfer interruption signal to said microprocessor~~

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

~~once the start of a new message has been acknowledged and recorded by said sending/receiving circuit when the microprocessor interruption signal is supplied,~~

said sending/receiving circuit also acknowledging the start of a following message while the interrupt signal is supplied,

said control circuitry for controlling said state latches preventing the binary information from said sending/receiving circuit from being written into said plurality of state latches during receipt of the start of the new message and during the presence of the interruption signal.

12. (Previously presented) The computer system of Claim 11 wherein said master apparatus and said slave apparatus communicate via a universal serial bus (USB) protocol.

13. (Previously presented) The computer system of Claim 11 further comprising at least one logic circuit for receiving the status signals from said sending/receiving circuit and setting said interruption state latch to a predetermined logic level to indicate a microprocessor interruption request.

14. (Previously presented) The computer system of Claim 11 wherein said master apparatus comprises a central processing unit.

15. (Previously presented) The computer system of Claim

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

11 wherein said slave apparatus comprises a computer peripheral.

16. (Previously presented) The computer system of Claim 11 further comprising a cable connecting said master apparatus and said slave apparatus.

17. (Currently amended) A slave apparatus for communicating with a master apparatus via a universal serial bus (USB) protocol, said slave apparatus comprising:

a sending/receiving circuit for sending and receiving binary information to and from the master apparatus and supplying status signals based thereon, ~~and for acknowledging and recording a new message only when a transfer interruption signal is not supplied;~~

a plurality of state latches and control circuitry cooperating therewith for receiving the status signals from said sending/receiving circuit and supplying state signals of said sending/receiving circuit based thereon;

a microprocessor for processing applications of the slave apparatus and also for processing the binary information received by said sending/receiving circuit when an interruption signal is supplied; and

an interruption state latch and a control circuit cooperating therewith for supplying an interruption signal to said microprocessor once the ~~end of a message has been acknowledged and for supplying the transfer interruption signal to said microprocessor once the start of a new message has been~~

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

acknowledged and recorded by said sending/receiving circuit when
~~the microprocessor interruption signal is supplied;~~

said sending/receiving circuit also acknowledging the
start of a following message while the interrupt signal is
supplied.

18. (Previously presented) The slave apparatus of Claim 17 wherein said control circuit for controlling said interruption state latch comprises at least one logic circuit for receiving the status signals from said sending/receiving circuit and setting said interruption state latch to a predetermined logic level to indicate a microprocessor interruption request.

19. (Previously presented) The slave apparatus of Claim 17 wherein said control circuitry for controlling said state latches prevents the binary information from said microprocessor from being written into said plurality of state latches during receipt of the start of the new message and during the presence of the interruption signal.

20. (Currently amended) A method of processing interruptions in a slave apparatus for communicating with a master apparatus via a universal serial bus (USB) protocol, the method comprising:

sending and receiving binary information to and from the master apparatus via a sending/receiving circuit and supplying status signals based thereon, ~~the sending/receiving~~

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

~~circuit acknowledging and recording a new message only when a transfer interruption signal is not supplied;~~

generating state signals of the sending/receiving circuit based upon the status signals;

processing applications of the slave apparatus and also processing the binary information received by the sending/receiving circuit when an interruption signal is supplied; and

supplying an interruption signal to a microprocessor of the slave apparatus once the ~~end of a message has been acknowledged and for supplying the transfer interruption signal to said microprocessor once the~~ start of a new message has been acknowledged and recorded by the sending/receiving circuit when the microprocessor interruption signal is supplied; and

sending an acknowledgement from the sending/receiving circuit to the master apparatus acknowledging the start of a following message while the interrupt signal is supplied.

21. (Previously presented) The method of Claim 20 wherein supplying the interruption signal comprises setting an interruption state latch to a predetermined logic level based upon the status signals to indicate a microprocessor interruption request.

22. (Currently amended) A method of processing interruptions in a slave apparatus for communicating with a master apparatus via a universal serial bus (USB) protocol, the method comprising:

In re Patent Application of:
MARIAUD ET AL.
Serial No. 09/989,317
Filing Date: NOVEMBER 20, 2001

generating a state signal indicating the end of a message;

detecting a start of a new message from the master apparatus and producing a start of message state signal;

acknowledging and recording the new message if a transfer interruption signal is not supplied;

supplying the transfer interruption signal to the microprocessor once the start of a new message has been acknowledged and recorded;

generating a signal indicating completion of recordation of the data from the start of the new message; ~~and~~

generating an interruption signal for a microprocessor of the slave apparatus in the presence of the state signal indicating the end of the message, the start of message state signal, and the signal indicating completion of recordation of the data from the start of the new message when the microprocessor interruption signal is supplied; and

acknowledging the start of a following message while the interruption signal is supplied.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.